

Aromatic 150

Product Specification - Version 1 dated January 1, 2016

Characteristic	Specification	Test Method
Specific Gravity, 20/20°C	0.880 - 0.895	ASTM D1298
Aniline Pt (mixed), °C	15 max.	ASTM D611
Color, Saybolt	30 min.	ASTM D156
Aromatic, vol. %	98.0 min.	ASTM D1319
Distillation, °C IBP DP	177 min. 215 max.	ASTM D1078
Flash Point, °C	62 min.	ASTM D93
Kauri-Butanol Value	90 min.	ASTM D1133
Sulfur, ppm	5 max.	ASTM D3120
Copper Corrosion	1 or 1A	ASTM D849
Notes: None		

www.SolventsandPetroleum.com

The preceding data is based on tests and experience, which Solvents and Petroleum Service, Inc. believes reliable, and is supplied for informational purposes only. Solvents and Petroleum Service, Inc. expressly disclaims any liability whatsoever for damage or injury which results from the use of the preceding data and nothing contained herein shall constitute a guarantee, warranty, or representation (including freedom from patent liability) by Solvents and Petroleum Service, Inc. with respect to the data, the product described, or its fitness for use for any specific purpose, even if that purpose is known to Solvents and Petroleum Service, Inc.

For detailed safety and handling information regarding these products, please refer to the respective Solvents and Petroleum Service, Inc. Safety Data Sheets (SDS).