

Diisobutyl Ketone

Product Specification - Version 1 dated November 16, 2015

Characteristic	Specification	Test Method
Specific Gravity, 20/20 °C	0.807 - 0.815	ASTM D268
Distillation, °C IBP Dry Point	163 min. 176 max.	ASTM D1078
Acidity as Acetic Acid, % wt.	0.02	ASTM D1613
Water, wt. %	0.2 max.	ASTM D1364
DIBK & DIBK isomers, wt. %	90.0 min.	-
Alcohol, wt. %	2.0 max.	-
Color, Pt-Co	20 max.	D1209
Shipping Data		
Pounds per Gallon, 20 °C	6.72	-
Kg per Liter, 20 °C	0.81	-
Flash Point, °F (T.C.C.)	120 (49 °C)	-
DOT Label Required	None	-
Notes: None		

www.SolventsandPetroleum.com

The preceding data is based on tests and experience, which Solvents and Petroleum Service, Inc. believes reliable, and is supplied for informational purposes only. Solvents and Petroleum Service, Inc. expressly disclaims any liability whatsoever for damage or injury which results from the use of the preceding data and nothing contained herein shall constitute a guarantee, warranty, or representation (including freedom from patent liability) by Solvents and Petroleum Service, Inc. with respect to the data, the product described, or its fitness for use for any specific purpose, even if that purpose is known to Solvents and Petroleum Service, Inc.

For detailed safety and handling information regarding these products, please refer to the respective Solvents and Petroleum Service, Inc. Safety Data Sheets (SDS).