

## Hexane

Product Specification - Version 1 dated January 1, 2015

Characteristic	Specification	Test Method
n-Hexane, vol. %	70.0 max.	Gas Chromatography
Sulfur, ppm	2 max.	ASTM D1266
Color, Saybolt	30 min.	ASTM D156
Appearance	Bright and Clear	Visual
Bromine Index, vol. %	0.003 max.	ASTM D1159
Specific Gravity, 15.6/15.6 °C	0.660 - 0.690	ASTM D369
Distillation, °F		
IBP	65.0 min.	ASTM D1078
DP	70.0 max.	
Non-volatile matter, g/100mL	0.001 max.	ASTM D1353
Notes: None		

[www.SolventsandPetroleum.com](http://www.SolventsandPetroleum.com)

The preceding data is based on tests and experience, which Solvents and Petroleum Service, Inc. believes reliable, and is supplied for informational purposes only. Solvents and Petroleum Service, Inc. expressly disclaims any liability whatsoever for damage or injury which results from the use of the preceding data and nothing contained herein shall constitute a guarantee, warranty, or representation (including freedom from patent liability) by Solvents and Petroleum Service, Inc. with respect to the data, the product described, or its fitness for use for any specific purpose, even if that purpose is known to Solvents and Petroleum Service, Inc.

For detailed safety and handling information regarding these products, please refer to the respective Solvents and Petroleum Service, Inc. Safety Data Sheets (SDS).