# **SAFETY DATA SHEET**

SOLVENTS & PETROLEUM
SERVICE
Experts in chemicals. Partners in business.

Version 1.0 Date 06/01/2015

#### 1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : Isopropyl alcohol 99.9%

CAS-No. : 67-63-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Company : Solvents and Petroleum Service, Inc.

1405 Brewerton Rd. Syracuse, NY 13208

Telephone : 800-315-4467

Fax : 315-454-8230

1.4 Emergency telephone number

Emergency Phone # : Chemtrec 800-424-9300

#### 2. HAZARDS IDENTIFICATION

## 2.1 Classification of the substance or mixture

## GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Eve irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 GHS Label elements, including precautionary statements

Hazard statement(s)

Pictogram

Signal word

H225
 H319
 H336
 Highly flammable liquid and vapor.
 Causes serious eye irritation.
 May cause drowsiness or dizziness.

Danger

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face

protection.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated

clothing. Rinse skin with water/ shower.

P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/ physician if you feel unwell.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for

extinction.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

## 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

May form explosive peroxides.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances

Synonyms : 2-Propanol

sec-Propyl alcohol Isopropyl alcohol Isopropanol

Formula : C<sub>3</sub>H<sub>8</sub>O 
Molecular weight : 60.10 g/mol 
CAS-No. : 67-63-0 
EC-No. : 200-661-7 
Index-No. : 603-117-00-0

**Hazardous components** 

Component	Classification	Concentration
2-Propanol		
	Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3; H225, H319, H336	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### **General advice**

Move out of dangerous area, consult a physician. Show this safety data sheet to the doctor in attendance.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

## In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

#### 5. FIREFIGHTING MEASURES

### 5.1 Extinguishing media

## Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

### 5.2 Special hazards arising from the substance or mixture

Carbon oxides

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

Use water spray to cool unopened containers.

## 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

## 6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

#### 6.4 Reference to other sections

For disposal see section 13.

#### 7. HANDLING AND STORAGE

## 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.

For precautions see section 2.2.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Handle and store under inert gas. hygroscopic

## 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
2-Propanol	67-63-0	TWA	200.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Central Nervous System impairment		

Upper Respiratory Tract irritation Eye irritation Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen  TWA  200 ppm  USA. ACGIH Threshold Limit Values (TLV)  Central Nervous System impairment Upper Respiratory Tract irritation Eye irritation Substances for which there is a Biological Exposure Index or Indices (see BEI® section)			
Not classifiat	ifiable as a human carcinogen  400 ppm USA. ACGIH Threshold Limit Valu		
	• •	(TLV)	
Central Nervous System impairment Upper Respiratory Tract irritation Eye irritation Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen			
STEL	400.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)	
Central Nervous System impairment Upper Respiratory Tract irritation Eye irritation Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Not classifiable as a human carcinogen			
TWA	400.000000 ppm 980.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants	
	mg/m3 is approxim		
TWA	400.000000 ppm 980.000000 mg/m3	USA. NIOSH Recommended Exposure Limits	
ST	500.000000 ppm 1,225.000000 mg/m3	USA. NIOSH Recommended Exposure Limits	

_ biological occupational exposure limits					
Component	CAS-No.	Parameters	Value	Biological specimen	Basis
2-Propanol	67-63-0	Acetone	40.0000 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift at	end of work	week	_

#### 8.2 **Exposure controls**

Appropriate engineering controls
Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

## Personal protective equipment

## Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

## Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm Break through time: 480 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.2 mm Break through time: 60 min

Material tested: Dermatril® P (KCL 743 / Aldrich Z677388, Size M)

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

## **Body Protection**

impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

## Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

## Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Color: colorless

b) Odor alcohol-like

c) Odor Threshold No data availabled) pH No data available

e) Melting point/freezing Melting point/range: -89.5 °C (-129.1 °F) - lit.

point

f) Initial boiling point and 82 °C (180 °F) - lit.

boiling range

g) Flash point 12.0 °C (53.6 °F) - closed cup

h) Evaporation rate 3.0

i) Flammability (solid, gas) No data available

j) Upper/lower Upper explosion limit: 12.7 %(V) flammability or Lower explosion limit: 2 %(V)

explosive limits

k) Vapour pressure 43.2 hPa (32.4 mmHg) at 20.0 °C (68.0 °F)

58.7 hPa (44.0 mmHg) at 25.0 °C (77.0 °F)

I) Vapour density No data available

m) Relative density 0.785 g/cm3 at 25 °C (77 °F)

n) Water solubility completely soluble

Partition coefficient: n-

octanol/water

log Pow: 0.05

p) Auto-ignition 425.0 °C (797.0 °F) temperature

q) Decomposition temperature

No data available

r) Viscosity No data available
 s) Explosive properties No data available
 t) Oxidizing properties No data available

9.2 Other safety information

Surface tension 20.8 mN/m at 25.0 °C (77.0 °F)

## 10. STABILITY AND REACTIVITY

#### 10.1 Reactivity

No data available

## 10.2 Chemical stability

Test for peroxide formation before distillation or evaporation. Test for peroxide formation or discard after 1 year. Stable under recommended storage conditions.

## 10.3 Possibility of hazardous reactions

Vapors may form explosive mixture with air.

#### 10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

#### 10.5 Incompatible materials

Oxidizing agents, Acid anhydrides, Aluminum, Halogenated compounds, Acids

## 10.6 Hazardous decomposition products

Other decomposition products - No data available

In the event of fire: see section 5

### 11. TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects

## **Acute toxicity**

LD50 Oral - Rat - 5,045 mg/kg

Remarks: Behavioral: Altered sleep time (including change in righting reflex). Behavioral: Somnolence (general depressed activity).

LC50 Inhalation - Rat - 8 h - 16000 ppm

LD50 Dermal - Rabbit - 12,800 mg/kg

No data available

#### Skin corrosion/irritation

Skin - Rabbit

Result: Mild skin irritation

### Serious eye damage/eye irritation

Eves - Rabbit

Result: Eye irritation - 24 h

#### Respiratory or skin sensitization

No data available

#### Germ cell mutagenicity

No data available

### Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (2-Propanol)

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by OSHA.

## Reproductive toxicity

No data available

No data available

### Specific target organ toxicity - single exposure

Inhalation, Oral - May cause drowsiness or dizziness.

### Specific target organ toxicity - repeated exposure

No data available

## **Aspiration hazard**

No data available

## **Additional Information**

RTECS: NT8050000

Central nervous system depression, prolonged or repeated exposure can cause:, Nausea, Headache, Vomiting, narcosis, Drowsiness, Overexposure may cause mild, reversible liver effects., Aspiration may lead to:, Lung oedema, Pneumonia

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Kidney - Irregularities - Based on Human Evidence Kidney - Irregularities - Based on Human Evidence

## 12. ECOLOGICAL INFORMATION

## 12.1 Toxicity

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 9,640.00 mg/l - 96 h

Toxicity to daphnia and

other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 5,102.00 mg/l - 24 h

Immobilization EC50 - Daphnia magna (Water flea) - 6,851 mg/l - 24 h

Toxicity to algae EC50 - Desmodesmus subspicatus (green algae) - > 2,000.00 mg/l - 72 h

EC50 - Algae - > 1,000.00 mg/l - 24 h

## 12.2 Persistence and degradability

No data available

#### 12.3 **Bioaccumulative potential**

No bioaccumulation is to be expected (log Pow <= 4).

#### 12.4 **Mobility in soil**

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

No data available

## 13. DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Packing group: II

## **Contaminated packaging**

Dispose of as unused product.

#### 14. TRANSPORT INFORMATION

DOT (US)

UN number: 1219 Class: 3

Proper shipping name: Isopropanol

Reportable Quantity (RQ):

Poison Inhalation Hazard: No

**IMDG** 

IATA

UN number: 1219 Class: 3

Packing group: II EMS-No: F-E, S-D

Proper shipping name: ISOPROPANOL

UN number: 1219 Class: 3

Packing group: II

Proper shipping name: Isopropanol

## 15. REGULATORY INFORMATION

#### **SARA 302 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

## **SARA 313 Components**

The following components are subject to reporting levels established by SARA Title III, Section 313:

CAS-No. **Revision Date** 67-63-0 1987-01-01 2-Propanol

#### SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

### **Massachusetts Right To Know Components**

## Pennsylvania Right To Know Components

, , , , , , , , , , , , , , , , , , ,	CAS-No.	Revision Date
2-Propanol	67-63-0	1987-01-01

#### **New Jersey Right To Know Components**

<b>3</b>	CAS-No.	Revision Date
2-Propanol	67-63-0	1987-01-01

#### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

## **16. OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

Eye Irrit. Eye irritation Flam. Liq. Flammable liquids

H225 Highly flammable liquid and vapor.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

STOT SE Specific target organ toxicity - single exposure

## **HMIS Rating**

Health hazard: 2
Chronic Health Hazard: \*
Flammability: 3
Physical Hazard 0

## **NFPA** Rating

Health hazard: 2
Fire Hazard: 3
Reactivity Hazard: 0

#### **Further information**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Solvents and Petroleum Service, Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.