

SAFETY DATA SHEET

Version 1.0 Date 06/01/2015

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name : Methanol

CAS-No. : 67-56-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Company : Solvents and Petroleum Service, Inc.

1405 Brewerton Rd. Syracuse, NY 13208

Telephone : 800-315-4467 Fax : 315-454-8230

1.4 Emergency telephone number

Emergency Phone # : Chemtrec 800-424-9300

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Acute toxicity, Oral (Category 3), H301 Acute toxicity, Inhalation (Category 3), H331 Acute toxicity, Dermal (Category 3), H311

Specific target organ toxicity - single exposure (Category 1), H370

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word Danger

Hazard statement(s)

H225 Highly flammable liquid and vapor.

H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled

H370 Causes damage to organs.

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER or doctor/

physician. Rinse mouth.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated

clothing. Rinse skin with water/ shower.

P304 + P340 + P311 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing. Call a POISON CENTER or doctor/ physician.

P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.

P363 Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for

extinction.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Synonyms : Methyl alcohol

Formula : CH₄O

Molecular weight : 32.04 g/mol

CAS-No. : 67-56-1

EC-No. : 200-659-6

Index-No. : 603-001-00-X

Registration number : 01-2119433307-44-XXXX

Hazardous components

Component	Classification	Concentration
Methanol		
	Flam. Liq. 2; Acute Tox. 3; STOT SE 1; H225, H301 + H311 + H331, H370	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

lf swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labeling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510): Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Compensation with the replace Control parameters				
Component	CAS-No.	Value	Control parameters	Basis
Methanol	67-56-1	TWA	200.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Headache		

Nausea Dizziness Eye damage Substances for which there is a Biological Exposure Index or Indices (see BEI® section) Danger of cutaneous absorption		
STEL	250.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
(see BEI® se	for which there is a ection) taneous absorption	
TWA	200.000000 ppm 260.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
Potential for dermal absorption		
ST	250.000000 ppm 325.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
	dermal absorption	
TWA	200.000000 ppm 260.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
The value in	mg/m3 is approxim	nate.

Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Methanol	67-56-1	Methanol	15.0000 mg/l	Urine	ACGIH - Biological Exposure Indices (BEI)
	Remarks	End of shift (As	soon as po	ssible after exposure	ceases)

Derived No Effect Level (DNEL)

Derived No Effect Level (DNEL)				
Application Area	Exposure routes	Health effect	Value	
Workers	Skin contact	Long-term systemic effects	40mg/kg BW/d	
Consumers	Skin contact	Long-term systemic effects	8mg/kg BW/d	
Consumers	Ingestion	Long-term systemic effects	8mg/kg BW/d	
Workers	Skin contact	Acute systemic effects	40mg/kg BW/d	
Consumers	Skin contact	Acute systemic effects	8mg/kg BW/d	
Consumers	Ingestion	Acute systemic effects	8mg/kg BW/d	
Workers	Inhalation	Acute systemic effects	260 mg/m3	
Workers	Inhalation	Acute local effects	260 mg/m3	
Workers	Inhalation	Long-term systemic effects	260 mg/m3	
Workers	Inhalation	Long-term local effects	260 mg/m3	
Consumers	Inhalation	Acute systemic effects	50 mg/m3	
Consumers	Inhalation	Acute local effects	50 mg/m3	
Consumers	Inhalation	Long-term systemic effects	50 mg/m3	
Consumers	Inhalation	Long-term local effects	50 mg/m3	

Predicted No Effect Concentration (PNEC)

Trouble and Enter Controlling and Transport		
Compartment	Value	
Soil	23.5 mg/kg	
Marine water	15.4 mg/l	
Fresh water	154 mg/l	
Fresh water sediment	570.4 mg/kg	
Onsite sewage treatment plant	100 mg/kg	

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm Break through time: 480 min

Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm Break through time: 31 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Color: colorless

b) Odor pungent

c) Odor Threshold No data availabled) pH No data available

e) Melting point/freezing

point

Melting point/range: -98 °C (-144 °F)

f) Initial boiling point and

boiling range

64.7 °C (148.5 °F)

g) Flash point 9.7 °C (49.5 °F) - closed cup

h) Evaporation rate No data availablei) Flammability (solid, gas) No data available

j) Upper/lower Upper explosion limit: 36 %(V) flammability or Lower explosion limit: 6 %(V)

explosive limits

k) Vapor pressure 130.3 hPa (97.7 mmHg) at 20.0 °C (68.0 °F)

546.6 hPa (410.0 mmHg) at 50.0 °C (122.0 °F) 169.27 hPa (126.96 mmHg) at 25.0 °C (77.0 °F)

I) Vapor density 1.11

m) Relative density 0.791 g/mL at 25 °C (77 °F)

n) Water solubility completely miscible

o) Partition coefficient: n-

octanol/water

log Pow: -0.77

p) Auto-ignition 455.0 °C (851.0 °F) at 1,013 hPa (760 mmHg)

temperature

q) Decomposition temperature

No data available

r) Viscosity No data availables) Explosive properties Not explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

9.2 Other safety information

Minimum ignition energy 0.14 mJConductivity $< 1 \mu\text{S/cm}$ Relative vapor density 1.11

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Vapors may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Acid chlorides, Acid anhydrides, Oxidizing agents, Alkali metals, Reducing agents, Acids

10.6 Hazardous decomposition products

Other decomposition products - No data available

In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LDLO Oral - Human - 143 mg/kg

Remarks: Lungs, Thorax, or Respiration: Dyspnea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

LD50 Oral - Rat - 1,187 - 2,769 mg/kg

LC50 Inhalation - Rat - 4 h - 128.2 mg/l

LC50 Inhalation - Rat - 6 h - 87.6 mg/l

LD50 Dermal - Rabbit - 17,100 mg/kg

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation

Respiratory or skin sensitisation

Maximisation Test (GPMT) - Guinea pig Does not cause skin sensitisation. (OECD Test Guideline 406)

Germ cell mutagenicity

Ames test S. typhimurium Result: negative

in vitro assay fibroblast

Result: negative

Mutation in mammalian somatic cells.

Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)

Mouse - male and female

Result: negative

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a

known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

Damage to fetus not classifiable

Fertility classification not possible from current data.

Specific target organ toxicity - single exposure

Causes damage to organs.

Specific target organ toxicity - repeated exposure

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration hazard

No aspiration toxicity classification

Additional Information

RTECS: PC1400000

Methyl alcohol may be fatal or cause blindness if swallowed.

Effects due to ingestion may include:, Headache, Dizziness, Drowsiness, metabolic acidosis, Coma, Seizures.

Symptoms may be delayed., Damage of the:, Liver, Kidney

Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to fish mortality LC50 - Lepomis macrochirus (Bluegill) - 15,400.0 mg/l - 96 h

NOEC - Oryzias latipes - 7,900 mg/l - 200 h

Toxicity to daphnia and

other aquatic invertebrates

Toxicity to algae

EC50 - Daphnia magna (Water flea) - > 10,000.00 mg/l - 48 h

Growth inhibition EC50 - Scenedesmus capricornutum (fresh water algae) -

22,000.0 mg/l - 96 h

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 5 d

Result: 72 % - rapidly biodegradable

Biochemical Oxygen

Demand (BOD)

600 - 1,120 mg/g

Chemical Oxygen Demand (COD)

1,420 mg/g

The seasth and services

Theoretical oxygen

٠,

1,500 mg/g

12.3 Bioaccumulative potential

Bioaccumulation Cyprinus carpio (Carp) - 72 d

at 20 °C - 5 mg/l

Bioconcentration factor (BCF): 1.0

12.4 Mobility in soil

demand

Will not adsorb on soil.

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

Additional ecological information

Avoid release to the environment.

....ommadon

Stability in water

at 19 °C83 - 91 % - 72 h

Remarks: Hydrolyses on contact with water. Hydrolyses readily.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1230 Class: 3 Packing group: II

Proper shipping name: Methanol Reportable Quantity (RQ): 5000 lbs

Poison Inhalation Hazard: No

IMDG

UN number: 1230 Class: 3 (6.1) Packing group: II EMS-No: F-E, S-D

Proper shipping name: METHANOL

IATA

UN number: 1230 Class: 3 (6.1) Packing group: II

Proper shipping name: Methanol

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

 CAS-No.
 Revision Date

 Methanol
 67-56-1
 2007-07-01

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

 CAS-No.
 Revision Date

 Methanol
 67-56-1
 2007-07-01

Pennsylvania Right To Know Components

 CAS-No.
 Revision Date

 Methanol
 67-56-1
 2007-07-01

New Jersey Right To Know Components

CAS-No. Revision Date Methanol 67-56-1 2007-07-01

California Prop. 65 Components

WARNING: This product contains a chemical known to the CAS-No. Revision Date State of California to cause birth defects or other reproductive 67-56-1 2012-03-16

harm. Methanol

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Acute Tox. Acute toxicity
Flam. Liq. Flammable liquids

H225 Highly flammable liquid and vapor.

H301 Toxic if swallowed.

H301 + H311 + Toxic if swallowed, in contact with skin or if inhaled

H331

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H370 Causes damage to organs.

HMIS Rating

Health hazard: 2
Chronic Health Hazard: *
Flammability: 3
Physical Hazard 0

NFPA Rating

Health hazard: 2
Fire Hazard: 3
Reactivity Hazard: 0

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Solvents and Petroleum Service, Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.