

Xylene

Product Specification - Version 1 dated January 1, 2015

Characteristic	Specification	Test Method
Total Aromatics, vol. %	99.0 min.	ASTM D1319
Color, APHA (Pt-Co)	20 max.	ASTM D1209
Specific Gravity, 20/20 °C	0.8600 - 0.8750	ASTM D369
Benzene, ppm	300 max.	Gas Chromatography
Distillation Range @ 760mm, °C IBP DP	137.0 min. 143.9 max.	ASTM D1078
Water Content, ppm	1000 max.	K-F Titration
Kauri-Butanol Value (Typical)	98	ASTM D1133
Flash Point, °F	80	ASTM D56
Notes: None		

www.SolventsandPetroleum.com

The preceding data is based on tests and experience, which Solvents and Petroleum Service, Inc. believes reliable, and is supplied for informational purposes only. Solvents and Petroleum Service, Inc. expressly disclaims any liability whatsoever for damage or injury which results from the use of the preceding data and nothing contained herein shall constitute a guarantee, warranty, or representation (including freedom from patent liability) by Solvents and Petroleum Service, Inc. with respect to the data, the product described, or its fitness for use for any specific purpose, even if that purpose is known to Solvents and Petroleum Service, Inc.

For detailed safety and handling information regarding these products, please refer to the respective Solvents and Petroleum Service, Inc. Safety Data Sheets (SDS).