

Brake Wash

Product Specification - Version 7/31/2020

Specifications	Minimum	Maximum
Solubility in Water	None	None
Specific Gravity @20/20°C	0.680	0.690
Water (wt%)	None	None
Flash Point	22 F	26 F
Boiling Point	207 F	210 F
Evaporation Rate	3.18 (butyl acetate=1)	-
Lower Explosive Limit	1.05%	-
Upper Explosive Limit	-	6.7%
Vapor Pressure	-	4.6 kPa
Vapor Density	-	3.46
Odor	Typical	
Appearance	Colorless	
Notes:	This solvent blend of heptane and acetone is fast drying and used in the automotive industry to clean brakes and associated parts.	

www.SolventsandPetroleum.com

The preceding data is based on tests and experience, which Solvents and Petroleum Service, Inc. believes reliable, and is supplied for informational purposes only. Solvents and Petroleum Service, Inc. expressly disclaims any liability whatsoever for damage or injury which results from the use of the preceding data and nothing contained herein shall constitute a guarantee, warranty, or representation (including freedom from patent liability) by Solvents and Petroleum Service, Inc. with respect to the data, the product described, or its fitness for use for any specific purpose, even if that purpose is known to Solvents and Petroleum Service, Inc.

For detailed safety and handling information regarding these products, please refer to the respective Solvents and Petroleum Service, Inc. Safety Data Sheets (SDS).