

# Exxsol™ D3135 Naphtha

## Dearomatized Fluid

General	
Availability <sup>1</sup>	▪ North America
Appearance	▪ Clear/Transparent
Form(s)	▪ Liquid
Revision Date	▪ November 2010

Properties	Typical Value (English)	Typical Value (SI)	Test Based On
Distillation Range			ASTM D86
Initial Boiling Point (IBP)	322 °F	161 °C	
Dry Point (DP)	352 °F	178 °C	
Flash Point	111 °F	44 °C	ASTM D56
Aromatic Content	4E-2 wt%	4E-2 wt%	ExxonMobil Method
Density (60.0°F (15.6°C))	6.47 lb/gal	0.775 g/ml	ASTM D4052
Vapor Pressure (68.0°F (20.0°C))	2 mm Hg	0.2 kPa	ExxonMobil Method
Aniline Point (Method E)	153 °F	67 °C	ASTM D611
Kinematic Viscosity (77.0°F (25.0°C))	1.27 cSt	1.27 mm <sup>2</sup> /s	ASTM D445

### Legal Statement

This product, including the product name, shall not be used or tested in any medical application without the prior written acknowledgement of ExxonMobil Chemical as to the intended use.

### Notes

Typical properties: these are not to be construed as specifications.

The values indicated in this document may deviate from the test method requirements by the number of significant figures shown.

<sup>1</sup> Product may not be available in one or more countries in the identified Availability regions. Please contact your Sales Representative for complete Country Availability.

For additional technical, sales and order assistance: [www.exxonmobilchemical.com/ContactUs](http://www.exxonmobilchemical.com/ContactUs)

**Worldwide and the Americas**  
ExxonMobil Chemical Company  
13501 Katy Freeway  
Houston, TX 77079-1398  
USA

**Asia Pacific**  
ExxonMobil Chemical Asia Pacific  
1 HarbourFront Place  
#06-00 HarbourFront Tower One  
Singapore 098633

**Europe, Middle East and Africa**  
ExxonMobil Chemical Europe  
Hermeslaan 2  
1831 Machelen, Belgium

©2014 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Chemical" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.