

Isopropanol

Product Specification - Version 1 dated 11/10/2015

Property	Specification	Result	Test Method
Appearance	Clear and Free of Suspended Matter	Passes	Visual
Color, Pt-Co	10 max	< 5	ASTM D1209
Water, wt. %	0.1 max	0.01	ASTM D1364
Acidity as Acetic Acid, wt. %	0.001 max	0.0007	ASTM D1613
Isopropanol, wt. %	99.96 min	99.99	GC L-227
Distillation AT 101.3kPa, °C Initial Boiling Point Dry Point	typ. 82.0 typ. 83.0	82.1 82.6	ASTM D1078
Density @ 20°C	typ. 0.784 - 0.786	0.7850	ASTM D4052
Refractive Index nD20	1.376 - 1.378	1.3770	ASTM D1218
Nonvolatile Matter, mg/100mL	1 max	0.1	ASTM D1353
Notes: None.			

www.SolventsandPetroleum.com

The preceding data is based on tests and experience, which Solvents and Petroleum Service, Inc. believes reliable, and is supplied for informational purposes only. Solvents and Petroleum Service, Inc. expressly disclaims any liability whatsoever for damage or injury which results from the use of the preceding data and nothing contained herein shall constitute a guarantee, warranty, or representation (including freedom from patent liability) by Solvents and Petroleum Service, Inc. with respect to the data, the product described, or its fitness for use for any specific purpose, even if that purpose is known to Solvents and Petroleum Service, Inc.

For detailed safety and handling information regarding these products, please refer to the respective Solvents and Petroleum Service, Inc. Safety Data Sheets (SDS).