

Safety DataSheet	Version: 1.0	Date: 06/01/2015
	1. Identification	
Product Name	KENSOL 30	
Recommended Use	Mineral Spirits is a widely-used solv asphalt reducer, hand cleaners, part applications.	
Company	Solvents and Petroleum Services, In 1405 Brewerton Rd	ю.
	Syracuse, NY 13208 800-315-4467	
	mark@solventsandpetroleum.com	
Emergency Telephone Number	Chemtrec 1-800-424-9300 (24HRS)	
	2. Hazards Identification	
GHS Classification	Flammable Liquids Category 3	
	Aspiration Hazard Category 1	
	Eye Irritation Category 2B	
	Skin Irritation Category 2	
	Specific Target Organ Toxicity-Sir	ngle Exposure (narcotic effects) –
	Category 3	
~	Static Accumulating Liquid	
Signal Word	WARNING	
Hazard Statements	Flammable liquid and vapor	
	May be fatal if swallowed and ente	ers airways.
	Causes eye irritation	
	Causes skin Irritation	
	May cause respiratory irritation; or	r May cause drowsiness or
	dizziness	
Other Hazard Information	Static accumulating liquid can bec	
	in bonded and grounded equipmen	
	Sparks may ignite liquid and vapor	
	Liquid conductivity is <100 pS/m	(picosiemans/meter) at 77°F
GHS Pictogram		
Precautionary Statements	Do not breathe mist or vapors	
	Use only outdoors or in a well-ve	entilated area

Date: 06/01/2015

2. Hazards Identification
If inhaled: Remove person to fresh air and keep comfortable for
breathing.
Call a poison center/doctor if you feel unwell.
If swallowed: immediately call a poison center or doctor.
Do NOT induce vomiting.
Store Locked up
Store in a well-ventilated place.
Wear protective gloves/clothing/eye protection/face protection
Keep away from heat/sparks/open flames/hot surfaces. –No
smoking
Keep container tightly closed
Ground/bond container and receiving equipment. This alone
may be insufficient to remove static electricity.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools
If on skin: take of immediately all contaminated clothing. Rinse
skin with water/shower.
Store in a well-ventilated place. Keep cool.
Wash thoroughly after handling.
If in eyes: rinse cautiously with water for several minutes. Remove
contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: get medical attention/advice.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
Dispose of contents in accordance with local/regional/national/
international regulations
3. Composition / Information on Ingredients

CAS No.	Component	Common Name	Percent

8052-41-3	Stoddard solvent	Mineral Spirits	100%

Hazardous Constituents contained in complex substances

CAS No.	Component	Common Name	Percent
111-84-2	Nonane	Nonane	1.0-7.0
25551-13-7	Trimethyl Benzene (mixed Isomers)	Hemellitene,	0.5-4.0
		Pseudocumene, mesitylene	

4. First Aid Measures

Eyes

Skin

Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately. In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Page 3 of 8

Date: 06/01/2015

4. First Aid Measures		
	Get medical attention immediately.	
Inhalation	Move exposed person to fresh air.	
Ingestion	DO NOT INDUCE VOMITING. If conscious, rinse out mouth with	
	water.	
Symptoms(Acute and delayed)	Exposure to high concentrations of vapors may cause irritation to the eyes, nose and throat, nausea, and dizziness.	
Note to Physicians	No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.	

5. Fire Fighting Measures

Suitable Extinguishing Media

Use dry chemical, CO₂, water spray (FOG) or foam

Unsuitable Extinguishing Media

Avoid solid water stream as it may scatter and spread fire.

Specific Hazards Arising from Chemical

Elevated temperatures can lead to the formation of irritating vapors. Decomposing products may include the following materials: Carbon dioxide and Carbon monoxide.

This product is a static accumulating liquid. Static accumulating liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor may cause flash fire. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminates. Restrict flow velocity to avoid build-up of static charge. Refer to NFPA 77, API 2003, and CENELEC CLC/TR 50404 for further guidance.

Protective Equipment and Precautions for Firefighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental Release Measures

Personal Precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

Environmental Precautions

Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas.

Methods for Containment

Stop leak if without risk. Use absorbent pads or earthen dams to contain.

Methods for Cleanup

A vapor suppressing foam may be used to reduce vapors. Cover liquid spill with sand, earth or other noncombustible absorbent material. Cover powder spill with plastic sheet or tarp to minimize spreading. Pick up and transfer to properly labeled container

7. Handling and Storage

Handling Procedures

Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated

7. Handling and Storage

clothing and protective equipment before entering eating areas. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Use non-sparking tools.

Shipping and Storing Procedures

Store in accordance with local regulations. Store in a segregated and approved area. Keep in the original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials. Do not store in unlabeled containers. Store and use away from heat, sparks, open flame or any other ignition source. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers that retain product residue may be hazardous. Incompatibilities:

Oxidizing Agents

		8. Expos	ure Contr	ols / Personal I	Protectio	n		
Component Exposure								
Stoddard Solvent		100		NT/A / 3	OTEL		OTEL	NT/A / 3
ACGIH TLV: OSHA PEL:	TWA: TWA:	100 ppm	TWA: TWA	N/A mg/m ³ 2900	STEL: STEL:	N/A ppm	STEL: STEL:	N/A mg/m ³ N/A mg/m ³
USHA PEL:	1 W A	500 ppm	IWA	mg/m^3	SIEL:	N/A ppm	SIEL:	N/A Ing/In
NIOSH REL:	TWA:	N/A ppm	TWA	350 mg/m^3	STEL:	N/A ppm	STEL:	N/A mg/m ³
NIOSH Ceiling:	18	$00 \text{ mg/m}^3 (15)$	5 minutes)	C				C
Nonane								
ACGIH TLV:	TWA:	200 ppm	TWA:	N/A mg/m ³	STEL:	N/A ppm	STEL:	N/A mg/m ³
Trimethyl Benzen	e (all iso	mers)						
ACGIH TLV:	TWA:	25 ppm	TWA:	N/A mg/m ³	STEL:	N/A ppm	STEL:	N/A mg/m ³
N/A signifies not availa	ble							
Engineering Controls		equip Mate in add or oth	ment. The rial should equate vent her enginee	a static accumu se alone may be be handled in e tilation. Use pre- gring controls to clow any recom	e insuffici enclosed ocess enclosed o keep wo	ent to remov vessels and ea losures, local rker exposur	e static ele quipment. exhaust v e to airbor	ectricity. Use only entilation
Eye/Face Protection				es and face shie		n statutory n	iiiits.	
Skin Protection			0 00	ant, imperviou		complying w	ith an app	proved
		stand	ard should	be worn at all nimize contact.	times. C			
Respiratory Protection General Hygiene	1	Use a an ap Respi levels Wash produ	properly f proved sta irator selects. hands, for acts, before	itted, air-purify ndard if a risk tion must be b rearms and face e eating, smokin iod. Appropria	ving or air assessme ased on k thorough ng and usi	nt indicated nown or ant ily after hand ng the lavato	this is near this is near this chemical sectors and at	cessary. xposure ical the end of

9. Physical and Chemical Properties

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Please see the Product Specification Sheet for further information.

	1 5	ee the Product Specification Sheet Jo	5 5
Appearance	Colorless	Flammability	Not Available
Physical State	Liquid	Upper/Lower	Not Available
		Flammability Limits	
Odor	Petroleum Solvent	Vapor Pressure (mm Hg	0.62
		at 20°C)	
Odor Threshold	Not Available	Vapor Density	Not Available
pH	Not Available	Relative Density (lbs/gal)	6.43
Melting/Freezing Point	Not Available	Water Soluble	No
(° F)			
Initial Boiling Point (F)	>640	Partition Coefficient: n-	Not Available
		octanol/water	
Boiling Range (F)	Not Available	Auto-ignition	Not Available
		Temperature (F)	
Flash Point (F)	105	Decomposition	Not Available
		Temperature (F)	
Evaporation Rate	Not Available	Viscosity (40°C mm ² /s)	1.8
_			
	1	4	1

10. Chemical Stability & Reactivity Information

Reactivity Chemical Stability	Polymerization will not occur Stable under normal conditions. If heated, product's static accumulation will rise and could cause flash fire.
Hazardous Reactions	None, under normal processing.
Conditions to Avoid	High temperatures, flames, sparks
Incompatibility	Strong acids and oxidizing materials
Hazardous Decomposition	Smoke, carbon monoxide, carbon dioxide, aldehydes and other products
Products	of incomplete combustion.

11. Toxicological Information	
-------------------------------	--

Acute Exposure Respiratory Irritation	An inhalation hazard may only arise if product is used in aerosol conditions or if heated up. If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and upper respiratory tract.
Eye Irritation Skin Irritation Sensitization Aspiration Hazard	Causes mild eye irritation that is reversible with proper care. Causes mild skin irritation that is reversible with proper care. Not expected to cause skin or respiratory sensitization. If swallowed can be aspirated into lungs and cause chemical pneumonia, varying degrees of pulmonary injury or death. If swallowed, do NOT induce vomiting.
Chronic Exposure Target Organ Effects	Vapor/aerosol concentrations above recommended exposure levels are irritating

Date:	06/	′01,	/2015)
-------	-----	------	-------	---

	to the eyes and respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects including death. Prolonged or repeated direct exposure to the skin results in symptoms of irritation and redness, dermatitis or oil acne.
Carcinogenicity	No data available to indicate product or any components present at greater than .1% are carcinogenic.
Mutagenicity	No data available to indicate product or any components present at greater than .1% are mutagenic or genotoxic.
Reproductive Toxicity	No data available to indicate either product or components present at greater than .1% that may cause reproductive toxicity.
Teratogenicity	No data available to indicate product or any components contained at greater than .1% may cause birth defects.

Analysis – LD50 / LC50

Inhalation LC50 Rat >5 mg/L (4Hr mist) **Oral LD50 Rat** mg/kg >5000 mg/kg **Dermal LD50 Rabbit** >2000

12. Ecological Information

Component Analysis- Ecotoxicity – Aquatic Life

Duration/Test	• •	Concentration/Conditions	5	
9	6 hr LL50	8.2	2	mg/L
Oncorhyne	cus mykiss			
4	8 hr EL50	3	2	mg/L
Oncorhyne	cus mykiss			
9	6 hr EL50	4	5	mg/L
Scenedesmus si	*			
Chronic Surviva	l NOELR	2.0	6	mg/L
Aquatic V	ertebrates			
Chronic Growt	h NOELR	2.0	6	mg/L
Aquatic Vertebrates				
			mg/L	
Daphnia magna				
Chronic Reproduction EL 50 10			0	mg/L
Daphnia magna				
Chronic reproduction NOELR 2.6			6	mg/L
Daphnia magna				
Persistence & Degradability	Inherentlybi	odegradable		
	NT / A 1111			

Persistence & Degradability	Inherently biodegradal
Bioaccumulation Potential	Not Available
Soil Mobility	Not Available
Other Adverse Effects	Not Available

13. Disposal Considerations

13. Disposal Considerations

The generation of waste should be avoided or minimized wherever possible. Treatment, storage, transportation and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

	14. Transportation Information				
Emergency Response Guide No.		No. 128	North American Emergency Response Guide Book		
	UN Number	Shipping Name (technical name)	Hazard Class	Packing Group	Labels/Placard
U.S. DOT Bulk (over 119 gallons)	1268	Petroleum Distillates, N.O.S. (Naphtha Solvent)	Combustible Liquid	III	1268
U.S. DOT Non-Bulk		Not Regulated			Exempt from labeling and placarding unless shipped via air or vessel
ΙΑΤΑ	1268	Petroleum Distillates, N.O.S. (Naphtha Solvent)	3	Π	FLAMMABLE LIQUID
IMDG	1268	Petroleum Distillates, N.O.S. (Naphtha Solvent)	3	III	1268 3

15. Regulatory Information

SARA Extremely Hazardous Substances (Sections 302 & 304)	This product does not contain greater than 1% of any "extremely hazardous substances" listed pursuant to Title III of the Superfund
	Amendments and Reauthorization Act of 1986 (SARA) Section 302 or
	Section 304 as identified in 40 CFR Part 355, Appendix A and B.
SARA Section 313	This product contains the following components in concentrations
	greater than 0.1% for carcinogenic substances and/or 1.0% of the
	substances subject to the reporting requirements of Section 313 of
	Title III of the Superfund Amendments and Reauthorization Act of
	1986 and 40 CFR Part 372:
	1,2,4 Trimethylbenzene (CASRN: 95-63-6): 2.7%

Date: 06/01/2015

15. Regulatory Informati	on		
SARA Section 311 & 312 Classifications		Acute Hazard	Yes
		Chronic Hazard	Yes
		Fire Hazard	Yes
		Reactivity Hazard	No
CERCLA	This product contains the following components listed under the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4: NONE		
California Prop 65	This product contains chemical(s) known to the state of California to cause cancer and/or birth defects.		

Global Chemical Inventories

Inventory				
US TSCA	Present*			
EU	Present			
Japan	Not available			
Australia	Present			
New Zealand	Present			
Canada	Present			
Switzerland	Not available			
Korea	Present			
Philippines	Present			
China	Present			
Taiwan	Not available			

* May be subject to TSCA 12b export notification. Contains Nonane (CASRN: 111-84-2) at 7 %.

16. Other Information			
US NFPA Ratings			
Health	Fire	Reactivity	
1	2	0	

HMIS Ratings

Health	Fire	Physical Hazards
1	2	0

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of SDS