



Odorless Mineral Spirits

Product Specification - Version 1 date January 1, 2015

Characteristic	Specification	Test Method
Specific Gravity, 20/20 °C	0.750 - 0.770	ASTM D1250
Distillation, °C IBP 50% Recovered DP	175 min. 193 max. 212 max.	ASTM D86
Color, Saybolt	+30 min.	ASTM D156
Aniline Point, °C	79 min.	ASTM D611
Flash Point, °C	51 min.	ASTM D56
Sulfur Content, ppm	5 max.	Microcoulometer
Appearance	Bright and Clear	Visual
Notes: None		

www.SolventsandPetroleum.com

The preceding data is based on tests and experience, which Solvents and Petroleum Service, Inc. believes reliable, and is supplied for informational purposes only. Solvents and Petroleum Service, Inc. expressly disclaims any liability whatsoever for damage or injury which results from the use of the preceding data and nothing contained herein shall constitute a guarantee, warranty, or representation (including freedom from patent liability) by Solvents and Petroleum Service, Inc. with respect to the data, the product described, or its fitness for use for any specific purpose, even if that purpose is known to Solvents and Petroleum Service, Inc.

For detailed safety and handling information regarding these products, please refer to the respective Solvents and Petroleum Service, Inc. Safety Data Sheets (SDS).