

1405 Brewerton Road • Syracuse NY 13208 Phone: 315-454-4467 | Fax: 315-454-8230 Toll Free: 1-800-315-4467

www.SolventsandPetroleum.com

Phosphoric Acid, Semi Grade

Specification Maximum Limits Assay (H3PO4) 85-87% Color (APHA) 10 Insoluble Matter 50 ppm **Reducing Substances** To pass test **Volatile Acids** 0.16 ueg/g Chloride (CI) 3 ppm Nitrate (NO₃) 5 ppm Sulfate (SO₄) 20 ppm Heavy Metals (as Pb) 5 ppm

Antimony (Sb) 20 ppm 0.5 ppm Arsenic (As) Calcium (Ca) 20 ppm Copper (Cu) 2 ppm Iron (Fe) 10 ppm Lithium (Li) 1 ppm Magnesium (Mg) 5 ppm Manganese (Mn) 0.5 ppm Nickel (Ni) 3 ppm 10 ppm Potassium (K) Sodium (Na) 15 ppm 5 ppm Strontium (Sr)

The preceding data is based on tests and experience, which Solvents and Petroleum Service, Inc. believes reliable, and is supplied for informational purposes only. Solvents and Petroleum Service, Inc. expressly dislaims any liability whatsoever for damage or injury which results from the use of the preceding data and nothing contained herein shall constitute a guarantee, warranty, or representation (including freedom from patent liability) by Solvents and Petroleum Service, Inc. with respect to the data, the product described, or its fitnesss for use for any specific purpose, even if that purpose is known to Solvents and Petroleum Service, Inc.

For detailed safety and handling information regarding these products, please refer to the respective Solvents and Petroleum Service, Inc. Safety Data Sheets (SDS).