

SAFETY DATA SHEET Version 1.0

Version 1.0 Date 06/18/2015

	RODUCT AND COMPANY	IDENTIFICATION		
1.1	Product identifiers Product name	Propyl Acetate		
	CAS-No.	: 109-60-4		
1.2	Relevant identified use	s of the substance or mixture and uses advised against		
	Identified uses	: Laboratory chemicals, Manufacture of substances		
1.3	Details of the supplier of the safety data sheet			
	Company	: Solvents and Petroleum Service, Inc. 1405 Brewerton Rd. Syracuse, NY 13208		
	Telephone Fax	: 800-315-4467		
	Emergency telephone r	: 315-454-8230		
1.4				

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Eye irritation (Category 2A), H319 Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336 Acute aquatic toxicity (Category 3), H402

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word



Hazard statement(s) H225 H319 H336 H402	Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. Harmful to aquatic life.
Precautionary statement(s) P210 P233 P240 P241 P242	Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools.

P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/ physician if you feel unwell.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Repeated exposure may cause skin dryness or cracking.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Formula	:	C ₅ H ₁₀ O ₂
Molecular weight	:	102.13 g/mol
CAS-No.	:	109-60-4
EC-No.	:	203-686-1
Index-No.	:	607-024-00-6

Hazardous components

Component	Classification	Concentration
Propyl acetate		
	Flam. Liq. 2; Eye Irrit. 2A; STOT SE 3; Aquatic Acute 3; H225, H319, H336, H402	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labeling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CÂS-No.	Value	Control parameters	Basis
Propyl acetate	109-60-4	TWA	200.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Upper Respiratory Tract irritation Eye irritation		n

TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)
Upper Resp Eye irritation	iratory Tract irritatio	n
STEL	250.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)
Eye irritation	iratory Tract irritatio	n
STEL	250 ppm	USA. ACGIH Threshold Limit Values (TLV)
Upper Resp Eye irritation	iratory Tract irritatio	n
TWA	200.000000 ppm 840.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
The value in	mg/m3 is approxin	nate.
TWA	200.000000 ppm 840.000000 mg/m3	USA. NIOSH Recommended Exposure Limits
ST	250.000000 ppm 1,050.000000 mg/m3	USA. NIOSH Recommended Exposure Limits

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Splash contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 110 min Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M)

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

		• •
a)	Appearance	Form: clear, liquid Color: colorless
b)	Odor	No data available
c)	Odor Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: -95 °C (-139 °F) - lit.
f)	Initial boiling point and boiling range	102 °C (216 °F) - lit.
g)	Flash point	14 °C (57 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 8 %(V) Lower explosion limit: 1.7 %(V)
k)	Vapor pressure	33 hPa (25 mmHg) at 20 °C (68 °F)
I)	Vapor density	3.53 - (Air = 1.0)
m)	Relative density	0.888 g/mL at 25 °C (77 °F)
n)	Water solubility	soluble
o)	Partition coefficient: n- octanol/water	log Pow: 1.23
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Oth	ner safety information	
	Surface tension	24.3 mN/m at 20 °C (68 °F)
	Relative vapor density	3.53 - (Air = 1.0)

10. STABILITY AND REACTIVITY

10.1 Reactivity

9.2

No data available

10.2 Chemical stability Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Vapors may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

- **10.5** Incompatible materials Oxidizing agents
- **10.6 Hazardous decomposition products** Other decomposition products - No data available In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 9,370 mg/kg Remarks: Behavioral: Somnolence (general depressed activity). Skin and Appendages: Other: Hair.

LC50 Inhalation - Rat - 4 h - 32 mg/l Remarks: No data available

LD50 Dermal - Rabbit - > 17,740 mg/kg

No data available

Skin corrosion/irritation Skin - Rabbit Result: No skin irritation

Serious eye damage/eye irritation

Eyes - Rabbit Result: Moderate eye irritation

Respiratory or skin sensitisation No data available

Germ cell mutagenicity No data available

Carcinogenicity

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

Additional Information RTECS: AJ3675000

prolonged or repeated exposure can cause:, narcosis

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 56 - 64 mg/l - 96 h

Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 318 mg/l - 24 h other aquatic invertebrates

- 12.2
 Persistence and degradability

 Biodegradability
 Result: Readily biodegradable
- **12.3 Bioaccumulative potential** Does not bioaccumulate.
- 12.4 Mobility in soil No data available

12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life.

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1276 Class: 3 Proper shipping name: n-Propyl acetate Reportable Quantity (RQ):	Packing group: II	
Poison Inhalation Hazard: No		
IMDG UN number: 1276 Class: 3 Proper shipping name: n-PROPYL ACETATE	Packing group: II	EMS-No: F-E, S-D
IATA UN number: 1276 Class: 3 Proper shipping name: n-Propyl acetate	Packing group: II	

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard

Massachusetts Right To Know Components

CAS-No.	Revision Date
109-60-4	1993-04-24
CAS-No.	Revision Date
109-60-4	1993-04-24
CAS-No.	Revision Date
109-60-4	1993-04-24
	109-60-4 CAS-No. 109-60-4 CAS-No.

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Aquatic Acute	Acute aquatic toxicity
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
H225	Highly flammable liquid and vapor.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H402	Harmful to aquatic life.
STOT SE	Specific target organ toxicity - single exposure

0

HMIS Rating

Health hazard:	2
Chronic Health Hazard:	
Flammability:	3
Physical Hazard	0
NFPA Rating	
Health hazard:	2
Fire Hazard:	3

File hazalu.	
Reactivity Hazard:	

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Solvents and Petroleum Service, Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.