

## Secondary Butyl Alcohol

Product Specification - Version 1 date January 1, 2015

Characteristic	Specification	Results
Purity, % (m/m)	≥ 99.00	passed
Moisture, % (m/m)	≤500	passed
Density, (20°C) Kg/l	0.806-0.807	passed
Distillation range, °C	78.5-81.0	passed
Non-Volatile Matter, mg/100ml	≤3	passed
Chroma Hezen	≤10	passed
Acidity (base on acetic acid), % (m/m)	≤0.001	passed
Notes: None		

[www.SolventsandPetroleum.com](http://www.SolventsandPetroleum.com)

*The preceding data is based on tests and experience, which Solvents and Petroleum Service, Inc. believes reliable, and is supplied for informational purposes only. Solvents and Petroleum Service, Inc. expressly disclaims any liability whatsoever for damage or injury which results from the use of the preceding data and nothing contained herein shall constitute a guarantee, warranty, or representation (including freedom from patent liability) by Solvents and Petroleum Service, Inc. with respect to the data, the product described, or its fitness for use for any specific purpose, even if that purpose is known to Solvents and Petroleum Service, Inc.*

*For detailed safety and handling information regarding these products, please refer to the respective Solvents and Petroleum Service, Inc. Safety Data Sheets (SDS).*